700XP 4 Hot Plate Electric Induction Cooking Top Range

Modular Cooking Range Line 700XP 4 Hot Plate Electric **Induction Cooking Top Range**

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



Modular Cooking Range Line

700XP 4 Hot Plate Electric Induction Cooking Top Range

371021 (E7INEH4000)

4 zone hot plate electric induction cooking top range -

371132 (E7INEH400N)

4 zone hot plate electric induction cooking top range -

Short Form Specification

Item No.

6 mm thick glass ceramic cooking surface with 4 independently controlled 3.5 kW induction zones. Induction top surface with seamless transition between individual heating zones. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- 6mm glass ceramic cooking surface with 4 independently controlled induction zones with a power of 3.5 kW per zone.
- Almost the entire surface of the ceramic plate can be used without "dead" spots.
- Indicating lamp for each zone located on control console.
- Induction plates endowed with overheating safety device.
- Power to the individual zones can be set with progressive output i.e. fine regulation at the lower and larger progress at the upper levels.
- Low heat dissipation to the kitchen.
- The smooth, glass ceramic plate is not directly heated, so there is no burning on cooking surface.
- IPX 4 water protection.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt

PNC 206135

PNC 206375

Optional Accessories

• 4 wheels, 2 swivelling with brake

Rear paneling - 1000mm (700/900)

(700/900XP). It is mandatory to install with base supports for feet/wheels.	
 Support for bridge type installation, 800mm 	PNC 206137 □
 Support for bridge type installation, 1000mm 	PNC 206138 □
 Support for bridge type installation, 1200mm 	PNC 206139
 Support for bridge type installation, 1400mm 	PNC 206140 □
 Support for bridge type installation, 1600mm 	PNC 206141 □
 Water column with swivel arm (water column extension not included) 	PNC 206289 □
• Water column extension for 700 line	PNC 206291 ☐
Chimney upstand, 800mm	PNC 206304
Right and left side handrails	PNC 206307
Base support for feet or wheels - 800mm (700/900)	PNC 206367
• Rear paneling - 800mm (700/900)	PNC 206374

APPROVAL	
----------	--



Modular Cooking Range Line 700XP 4 Hot Plate Electric Induction Cooking Top Range

Rear paneling - 1200mm (700/900)Chimney grid net, 400mm	PNC 206376 ☐ PNC 206400 ☐
 Frontal handrail, 800mm 	PNC 216047 □
 Frontal handrail, 1200mm 	PNC 216049 🗖
 Frontal handrail, 1600mm 	PNC 216050 🖵
• Large handrail - portioning shelf, 400mm	PNC 216185 🖵
• Large handrail - portioning shelf, 800mm	PNC 216186 🖵
• 2 side covering panels for top appliances	PNC 216277 🗖
 Stainless steel universal frying pan with stainless steel handle (diam. 200mm) suitable for induction and all other heating sources (only for 371021) 	PNC 653596 □
 Universal frying pan with stainless steel handle (diam. 240mm) suitable for induction and all other heating sources (only for 371021) 	PNC 653597 □
 Universal frying pan with stainless steel handle (diam. 280mm) suitable for induction and all other heating sources (only for 371021) 	PNC 653598 □





Modular Cooking Range Line 700XP 4 Hot Plate Electric Induction Cooking Top Range

Front Α0 (D) (D) 30 5/8 778 mm 0 7/16 " 0 7/16 11 mm 11 mm Top Α0 330 31 1/2 " 800 mm Electrical connection Side Α0 15/16 " 13 1/16 E 332 251 1 7/16 E Q 15/16 E 37 24 4 1/16 103 mm 5 7/8 17 11/16 ' 149 mm 450 mm

Electric

Supply voltage:

371021 (E7INEH4000) 400 V/3N ph/50/60 Hz **371132 (E7INEH400N)** 230 V/3 ph/50/60 Hz

Total Watts: 14 kW

Key Information:

Induction Top Dimensions (width): 800 mm
Induction Top Dimensions (depth): 730 mm
Net weight: 40 kg

Shipping weight:

371021 (E7INEH4000) 60 kg **371132 (E7INEH400N)** 68 kg

Shipping height:

371021 (E7INEH4000) 530 mm **371132 (E7INEH400N)** 540 mm

Shipping width:

371021 (E7INEH4000) 820 mm **371132 (E7INEH400N)** 830 mm **Shipping depth:** 850 mm

Shipping volume:

371021 (E7INEH4000) 0.37 m³ **371132 (E7INEH400N)** 0.38 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Induction compatible pots & pans must be used.

