

KM-40B Ice Machine

Product Features

- Individual premium crescent cube with no ice bridging
- Exceptionally hard crystal clear cubes that melt slowly
- Durable stainless steel exterior
- Slide in air filter at front for easy cleaning maintaining performance efficiency
- Double-sided stainless steel evaporator for all water conditions - produces more ice in less cycles
- Flush mount to rear wall
- Vertical pump motor
- Good in hard water areas
- Snap in water tank design easy to remove for sanitization
- Low electrical consumption
- Low water consumption
- LED lights and audible alarms
- Rated for tropical conditions 40°C ambient temperature
- 2 year Parts & Labour on entire unit



Simply the world's best ice™











Product Specifications

Model	Cooling	Weight	AC Supply Voltage	Refrigerant	Ambient	Water Temp	Water Pressure
KM-40B	Air	Net: 40kg Gross: 50kg	220-240V/ 50Hz	R134A/240g	1 – 40°C	5 – 35°C	0.07-0.8 MPa

Ask Hoshizaki representative for additional information if required

Ice Production Specifications

Ice Production per 24 hours (Air / Water)					
10°C/10°C 21°C/15°C 32°C/21°C		Ice Production per cycle	Freeze Cycle	Max Storage	
43kg	41kg	33kg	0.78kg/80pcs	25mins	16kg (Bin Cont Setting Approx 14kg)

Please Note: above are approximate











