

KM-55B Ice Machine

Product Features

- Individual premium crescent cube with no ice bridging
- Exceptionally hard crystal clear cubes that melt slowly
- Durable stainless steel exterior
- Slide in air filter at front for easy cleaning maintaining performance efficiency
- Double-sided stainless steel evaporator for all water conditions - produces more ice in less cycles
- Flush mount to rear wall
- Vertical pump motor
- Good in hard water areas
- Snap in water tank design easy to remove for sanitization
- Low electrical consumption
- Low water consumption
- LED Lights and audible alarms
- Rated for tropical conditions 40°C ambient temperature
- 2 year Parts & Labour on entire unit

Simply the world's best ice™







Product Specifications

Model	Cooling	Weight	AC Supply Voltage	Refrigerant	Ambient	Water Temp	Water Pressure
KM-55B	Air	Net: 46kg Gross: 58kg	220-240V/ 50Hz	R134A/240g	1 – 40°C	5 – 35°C	0.07-0.8 mPA

Ask Hoshizaki representative for additional information if required

Ice Production Specifications

Ice Productio (Air / Water)	n per 24 hours					
10°C/10°C	21°C/15°C	32°C/21°C	Ice Production per cycle	Freeze Cycle	Max Storage	
53kg	50kg	41kg	1.03kg /110pcs	28mins	23kg (Bin Cont Setting Approx 19kg)	

Please Note: above are approximate





