

**KU SERIES:- UNDERBENCH STORAGE SERIES**



**KUR9-1**  
**KUF9-1**



**KUR12-2**  
**KUF12-2**  
**KUF15-2**  
**KUF15-2**



**KUR18-3**  
**KUF18-3**

**FEATURES:**

- Designed to 32° C ambient operating temperature.
- 2 Years warranty
- Only requires one standard power point (GPO):- 240V 50Hz 10 amp.
- Digital Temperature Display.
- 1 height adjustable shelves per door. Individual shelves behind each door maximize storage configurations.
- Stainless steel construction for superior corrosion resistance.
- Stainless steel internal floor with covered corners allows for easy cleaning and sanitizing.
- Solid Doors. Designed with recessed handle and self closing hinging with 90° dwell feature.
- LED interior lighting
- One piece door gaskets, removable without tools for easy cleaning.
- Automatic energy efficient hot gas condensate disposal. No drainage required.

**MAIN DATA**

Specifications are subject to change without notice. E&OE.

Model	Temp	Doors	Net Volume (L)	Shelves	Dimensions W x D* x H (mm)	Power 220v 50Hz	Shipping Weight
<b>KUR9-1</b> Fridge	1-8° C	1	198	1	900w x 700d x 800h	314w	72
<b>KUF9-1</b> Freezer	-21 ~ -12° C	1	198	1	900w x 700d x 800h	366w	72
<b>KUR12-2</b> Fridge	1-8° C	2	311	2	1200w x 700d x 800h	314	84
<b>KUF12-2</b> Freezer	-21 ~ -12° C	2	311	2	1200w x 700d x 800h	366	84
<b>KUR15-2</b> Fridge	1-8° C	2	425	2	1500w x 700d x 800h	314	93
<b>KUF15-2</b> Freezer	-21 ~ -12° C	2	425	2	1500w x 700d x 800h	366	93
<b>KUR18-3</b> Fridge	1-8° C	3	538	3	1800w x 700d x 800h	366	109
<b>KUF18-3</b> Freezer	-21 ~ -12° C	3	538	3	1800w x 700d x 800h	613	109

## KU SERIES:- UNDERBENCH STORAGE SERIES

### Specification

- Electronic Controller:** Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.
  - High-tech Monitor:** The monitor digitally displays the present temperature. You can easily change the temperature by adjusting the thermostat.
  - Construction:** The Turbo Air cabinet boasts a stainless steel exterior (back and bottom ) and stainless steel interior with *all* inside walls and door liners. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The K Series can add a touch of style to the most refined setting.
  - Hot Gas Condensate System:** Through Turbo Air's creative innovation, the condensate
- system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.
- Door Pressure Release Device:** Pressure relief doors are designed to eliminate vacuum pressure and allows easy, instant door opening.
  - Insulation:** 50mm high density polyurethane foam, Blowing agent, Cyclopentane for CFC free Ozone protection and superior insulating properties.
  - Door:** 50mm high pressure injected polyurethane foam. Designed with recessed handle provides easy access.
  - Gasket:** PVC welded one piece magnetic gasket. Removable without tools for easy cleaning. And replacing
  - Hinging:** Self closing with 90° dwell open.
  - Shelves:** 1 adjustable, PVC coated, steel shelves per door.
  - Electrical:** Units come ready for connection to 220volt 50hz 10amp GPO. Single Outlet. It is recommended that a dedicated GPO be used.
  - Warranty:** Manufacturers warranty 24 month parts and labour.

1.terms and conditions apply. Visit web site for full details. [www.austwidesales.com.au](http://www.austwidesales.com.au) Specifications are subject to change without notice. E&OE. 20150426

### ELEVATIONS. (not to scale)

