



TECHNICAL DATA

| 2-4 bar |
|-----------------|
| 0 - 3 ° dH |
| |
| 9.5 kW 13.7 A |
| |
| <70 dB(A) |
| |

PRODUCT ADVANTAGES

- Uniform cooking process:
 - Oscillating fan
 - Separating grid between fan and cavity
 - With efficient ventilator
- Speed of the cooking process:
 - Efficient and fast steam production
 - Fast temperature transition due to an open grid
 - Rapid cool function
- Efficient automatic cleaning system:
 - Automatic, economic and fast
 - Programmes:
 - Short: 35 minutes
 - Medium: 43 minutes
 - Long: 51 minutes
 - Fast: 2 minutes water only
 - Rinsing: 20 minutes water only

- Crosswise loading enables easy handling, a better view and more safety
- Basic touch display with practical and intuitive icons
- Fan Control: 6 speeds
- Water injection technology and rapid cooling of the cavity
- Core Probe for accurate cooking

CONNECTIONS

| ① Fresh-water connection | 3/4" |
|----------------------------|--------------------------|
| ② Drain connection | 1" |
| ③ Power connection | 400 / 50 / 3 / N / PE |
| 4 Chemical hose | 1500 mm |
| ⑤ Equipotential connection | M6 |
| 6 Ventilation | |
| 7 Ventilation nozzle | |

DIMENSIONAL DRAWING

